

Turnstile ID Gate 1900 Single



Description

Our **ID GATE 1900 Single** is a turnstile that can be used in various application areas such as parking garages, airports, public transportation, as well as industrial and manufacturing facilities.

The ID GATE 1900 Single is also employed in stadiums to control access to the stadium or VIP areas. Overall, the ID GATE 1900 is a reliable solution for access control that contributes to enhancing the security and comfort of visitors



Manual control of entry direction



2080mm tall interior



-ully welded



90°/ 120° Rotor Optional (three or four sections)





Anti-trailing function: Only one person can pass at a time


HIGHTLIGHTS


- Durability
- High operational reliability
- Quick response
- One-sided or two-sided operation
- Automatic reset function (The turnstile is automatically locked within 5 seconds if the passenger delays entry)
- Automatic anti-panic function that guarantees free passage in emergency situations (e.g., power outage or fire alarm)
- Indoor and outdoor use
- LED status display
- 3-year warranty











TECHNICAL DATA

Specification	
Dimension	1460 x 1250 x 2180mm (L x W x H)
Passage width	625mm/passage
Direction	Single directional / Bi-directional
Material	Stainless steel (304)
Power supply	AC230V/110V, 50/60Hz
Power consumption	40W
Operating voltage	24V DC
Throughput frequency	30 people per minute
Emergency mechanism	Automatic opening of the turnstile
Communication interface	TCP/IP, RS485, dry contact, relay signal
Net weight	200kg/piece
Operating temperature	- 15 °C up to 60 °C
Optional	 RFID Reader (Mifare / EM / Hitag) Barcode / QR Code Reader Combined QR Code / RFID Remote control (cable / radio) Third party reader installation on request