

## Access reader ID INFO 5000



### Description

The Access reader, with an integrated camera, facilitates easy attendance recording of individuals using smart cards, smartphones, QR codes, or barcodes.

The innovative **ID INFO 5000** provides a modern and straightforward terminal solution for your rooms, premises, or events. Booking, managing, and tracking the individuals to be counted is effortlessly handled by the system. This terminal identifies both existing and new member and employee badges, supporting all current RFID technologies. You can manage the people-counting with or without unique assignment.

The ID INFO 5000 is a state-of-the-art touch terminal with backlighting, making it perfect for access control in leisure facilities like gyms, pools, or spas. Additionally, it's suitable for time recording in businesses. Identification at the terminal is achieved using contactless RFID data carriers, such as wristbands, cards, or key fobs. To log in and identify themselves at the terminal, users simply hold their chip card or smartphone up to the reader.

### APPLICATIONS

- Touch terminal for Access control
- Capture of RFID and/or Barcode
- 7" Touchscreen
- can be used in combination with our turnstiles usable

### HIGHLIGHTS

- Access control/ time recording
- Gym
- Baths / Spas
- Companies & Institutions
- cultural institutions, e.g. museums

### FREQUENCY RANGES

- HF (13,56 MHz):  
MIFARE, DESFire, LEGIC
- LF (125 kHz):  
Hitag 1/2, EM



## TECHNICAL DATA

Specifications	
Connections	1x RJ-45, 4x USB, RS232, RS485, Audio, 2x Relais 6x Digital Out 4x Digital In
Interfaces	Ethernet, WLAN, Bluetooth
Display	7" touch display capacity (800 x 480 pixels)
Camera	8 Megapixel, 1080p
RFID technology (freely selectable)	Mifare Classic, Mifare-DESFire, LEGIC prime, LEGIC adavant, LEGIC CTC, Hitag 1/2, EM
Frequency ranges	125 kHz & 13,56 MHz - Single or parallel
Operating system	Linux with local database (offline capable)
Size and weight	215x150x46 mm & ca. 900 g
Mounting options	Wall-mounted, stand (brushed stainless steel/stainless steel) Table-top unit, each upright or transverse
Wall mount	VESA standard 50x50 mm included
Power supply	12-60 V
Housing	Plastic (ABS)
Colors	Black (cf. RAL 9005), White (cf. RAL 9016)
Protection class	IP40 (with rubber sealing (TPE) IP65)

## ORDER CODE

VERSION	ORDER CODE
ID INFO 5000	R-EA-IN5000